

AWAYWASH

Concrete Washout System



- Concrete truck-mounted washout collection and retention system allowing to washout and transport harmful water away from construction sites.
- Capacity of 55L to top of sieve slots.
- Patented Design with EU Design registration.
- Mount with M8 Stainless Steel bolts - max screw length 15 mm + frame thickness; max frame hole \varnothing 10 mm. Tighten to a max torque of 25 Nm.
- Can be retro fit.
- Do not stand on the AWAYWASH or drill into the sump.
- Empty daily at appropriate disposal/recycling sites.
- Made from 100% recyclable chemically resistant PE.
- Inspect the unit daily, repair or replace if damaged.
- Wear protective PPE especially gloves when removing the sieve and washing down.
- Designed to fit primarily on the driver side of most right hand drive vehicles.
- Before driving ensure the flexible hose is firmly fitted and locked to the spigot.
- Always empty unit & hose at temperatures $\leq 3^{\circ}\text{C}$.
- Watch the AWAYWASH video for typical use and advice here:
https://www.youtube.com/watch?v=gBiOW2z_eqc



CCRT-S-YE



CCRT-S-YE



CCRT-S-YE



CCRT-TS-YE + CCRT-K



CCRT-TS-YE + CCRT-K



CCRT-S-YE

Queries / Informations / Anfragen / Preguntas

UK

Jonesco (Preston) Ltd
Pittman Way, Fulwood,
Preston PR2 9ZD
Lancashire, England

Tel. +44 (0) 1772 706888
Fax +44 (0) 1772 702209
e-mail:sales@jonesco-plastics .com

France

Jonesco S.A.R.L.,
SECLIN UNEXPO
1524 Avenue de l'Épinette
59113 Seclin, France

Tel :+33 (3) 20 32 11 11
Fax + 33 (0) 3 20 90 62 10
e-mail:jonesco@jonesco-fr.com

Deutschland

Jonesco

Tel +44 (0) 1772 706820
Fax +44 (0) 1772 702209
e-mail:sales@jonesco-plastics.com