



# AWAYWASH & AWAYWASH MK II

Concrete Washout System



Mount with M8 Stainless Steel bolts - max screw length 15 mm + frame thickness; max frame hole  $\varnothing$  10 mm. Tighten to a max torque of 25 Nm.

Do not stand on the AWAYWASH or drill into the sump.

Empty daily at appropriate disposal/recycling sites.

Inspect the unit daily, repair or replace if damaged.

Wear protective PPE especially gloves when removing the sieve and washing down.

Designed to fit primarily on the driver side of most right hand drive vehicles.

Before driving ensure the flexible hose is firmly fitted and locked to the spigot.

Always empty unit & hose at temperatures  $\leq 3^{\circ}\text{C}$ .

Watch the AWAYWASH video for typical usage and advice:

[https://www.youtube.com/watch?v=gBiOW2z\\_eqc](https://www.youtube.com/watch?v=gBiOW2z_eqc)



CCRT-S-YE



CCRT-S-YE



CCRT-S-YE

## Awaywash












## Awaywash MK II



## Sieve



	 EAN-13				 mm	 mm	 mm	 kg	
<b>CCRT-TS-YE</b>	5055644212017	✓	✓	-	525	1860	760	21.5	55
<b>CCRT2-TS-BK</b>	5055644216060	✓	✓	-	500	610	560	11	45
<b>CCRT2-TS-YE</b>	5055644216077	✓	✓	-	500	610	560	11	45
<b>CCRT-S-BK</b>	5055644216053	-	✓	-	240	385	385	1.5	-
<b>CCRT-S-YE</b>	5055644212031	-	✓	-	240	385	385	1.5	-
<b>CCRT-K</b>	5055644215018	-	-	✓	-	-	-	1.2	-

### Jonesco (Preston) Ltd

Pittman Way  
Fulwood  
Preston  
PR2 9ZD  
United Kingdom

Tel: +44 (0) 01772 706888

E-mail: [sales@jonesco-plastics.com](mailto:sales@jonesco-plastics.com)

### Jonesco (France)

Jonesco S.A.R.L.  
SECLIN ENEXPO  
1524 Avenue de l'Einette  
59113 Seclin  
France

Tel: +33 (3) 20 32 11 11

Email: [jonesco@jonesco-fr.com](mailto:jonesco@jonesco-fr.com)